










P.C.B LAYOUT (T=1.60mm)
VIEW BOTTOM (tolerance±0.05)

NOTES:

- MATERIAL
 - HOUSING: HI-TEMP PLASTIC (UL94-V-0), BLACK
 - CONTACT: COPPER ALLOY (T=0.20),
PLATING: GOLD PLATED ON CONTACT AREA,
TIN PLATED ON SOLDER TAILS, UNDER
NICKEL PLATED.
 - SHELL: BRASS (T=0.40), PLATING: NICKEL PLATED,
 - SPRING SHELL: STAINLESS SUS304 T=0.20mm
 - COVER: HI-TEMP, PLASTIC (UL94V-0) BLACK,
- SPECIFICATION:
 - CURRENT RATING: 0.5 A
 - CONTACT RESISTANCE: 30mΩ MAX.
 - DIELECTRIC WITHSTANDING VOLTAGE: 500V AC
R.M.S FOR ONE MINUTE.
 - INSULATION RESISTANCE: 100MΩ MIN AT 500V DC.
 - OPERATING TEMPERATURE: -25° TO +85°.
 - DURABILITY: 10000 CYCLES.
 - MATING FORCE: 4.5KG MAX.
 - UNMATING FORCE: 1.0KG MIN



GENERAL TOLERANCE		KINGCONN 皇海科技股份有限公司	
X± 0.50	X*± 5°	名 稱(TITLE) MINI DP FEMALE DIP+SMT TYPE	
.X± 0.30	.X*± 2°		
.XX± 0.20	.XX*± 1°		
單 位(UNIT)	料 號(PART NO.)	圖 號(DWG NO.)	
mm	7MNDP-F0-0001	7MNDP-F0-0001	
審 核(APPROVAL)	核 對(CHECKED)	製 圖(DRAWN)	比 對 SCALE 1:1
			張 數 SHEET 1/1
			更 改 REV A

